



# <u>SuperBundy Hot Melt Adhesive</u> Product Technical Data Sheet



### 1. Product Description:

SuperBundy Hot Melt adhesive is a solid system requiring no mixing or blending prior to use and specifically formulated for securely and permanently affixing safety devices to horizontal paved surfaces of roadways, parking lots, or raised islands.

SuperBundy is a non-toxic, zero Volatile Organic Compound (VOC) adhesive for use with delineator posts, curb sections, rumble strips, etc. SuperBundy has resilient characteristics which enable it to remain flexible throughout its lifetime and, therefore, acts as a shock absorber. SuperBundy is available in 8 x 8-inch pads. Each 8 x 8-inch pad is 0.10 inches (2.5mm) thick. The material can easily be cut into other shapes with scissors or a knife. SuperBundy comes standard in a light grey color. (Note: with posts, do not attempt to use singly as this could result in inadequate bonding and failure.)

### 2. Technical Data:

Component	CAS#	CONTENT
Pigments	Unknown	1 – 5%
Alkyd Resin	68333-62-0	5 – 20%
Polymers	Unknown	10 – 25%
Fillers	Unknown	35 – 75%

# 3. Packaging:

SuperBundy is packaged 25 pieces per box.

# 4. Surface Preparation:

Apply to clean, dry surfaces free of contaminants that can adversely affect adhesion.

#### 5. Storage Life:

For maximum shelf life, store indoors in original packaging below 80° Fahrenheit.

Pexco, Davidson Traffic Control